



PERFORMANCE DATA 50Hz

MODEL		P ₂		DELIVERY														n≈2850 1/min					
1 ~ 220V/240V	3 ~ 380V/415V	KW	HP	Q	m³/h	0	0.6	1.2	1.8	2.4	3.0	3.6	4.2	4.8	5.4	6.0							
					l/min	0	10	20	30	40	50	60	70	80	90	100							
4SDM4/3	4SD4/3	0.25	0.33	H(m)		22	21	20	19	19	17	16	14	11	8	5							
4SDM4/4	4SD4/4	0.37	0.5			29	28	27	26	25	23	21	18	15	11	6							
4SDM4/5	4SD4/5	0.37	0.5			36	35	34	32	31	29	26	23	18	13	8							
4SDM4/6	4SD4/6	0.55	0.75			43	42	40	39	37	35	32	27	22	16	9							
4SDM4/7	4SD4/7	0.55	0.75			51	49	47	45	44	41	37	32	26	19	11							
4SDM4/8	4SD4/8	0.75	1			58	56	54	52	50	47	42	36	29	21	12							
4SDM4/10	4SD4/10	0.75	1			72	69	67	65	62	58	53	46	37	27	16							
4SDM4/12	4SD4/12	1.1	1.5			87	83	80	78	75	70	63	55	44	32	19							
4SDM4/14	4SD4/14	1.1	1.5			101	97	94	91	87	82	74	64	51	37	22							
4SDM4/16	4SD4/16	1.5	2			116	111	107	104	100	93	84	73	59	43	25							
4SDM4/19	4SD4/19	1.5	2			137	132	127	124	118	111	100	87	70	51	30							
4SDM4/22	4SD4/22	2.2	3			159	153	147	143	137	128	116	100	81	59	34							
4SDM4/26	4SD4/26	2.2	3			188	181	174	169	162	152	137	118	95	69	40							
-	4SD4/30	3	4			217	208	201	195	187	175	158	137	110	80	47							
-	4SD4/34	3	4			246	236	228	221	212	198	179	155	125	91	53							
-	4SD4/39	4	5.5			282	271	261	254	243	228	206	178	143	104	61							
-	4SD4/44	4	5.5			318	306	295	286	274	257	232	200	161	117	68							
-	4SD4/49	5.5	7.5			354	340	328	319	305	286	259	223	180	131	76							
-	4SD4/54	5.5	7.5			390	375	362	351	336	315	285	246	198	144	84							