Technical data
CMP 76

Revision no	Page:
	1

Receiver	From
Company name	
Respons. Department	
Person in charge	
Phone number	
Fax no	
E-mail address	



Operating data specification

Nominal flow	m³/h	0
Nominal head	m	0
Static head	m	0
NPSH - value of plant	m	0
Inlet pressure	bar	0,09793
Fluid		Water, pure
Operating temperature t A	°C	20
Density at t A	kg/m³	998,3
Kin. viscosity at t A	mm²/s	1,005

Pump

Pump name		CMP 76	
Size			
Design			
Speed rpm	2850	No of stages	1
Impeller type		Single vane impeller	
Flow	Nominal	m³/h	
	Max-	m³/h	6,03
	Min-	m³/h	0
Head	Nominal	m	
	Max-	m	30
	Min-	m	21
Head H(Q=0)		m	30
NPSH 3%		m	
Max. working pressure		bar	2,94
Shaft power		kW	
Efficiency		%	
Max absorbed power		kW	0,63914

Materials Pump

Shaft	Stainless steel AISI 420 (1.4028)
Impeller	Thermoplastic resin
Pump body	Cast iron EN-GJL-200
Support	Aluminium
OR	NBR Rubber
Mechanical seal	BXPG (Gra/Cer/NBR)

Motor					
Manufacturer / Type		SAER 71 2 - 0,55 1~			
Rated power	kW	0,55	Efficiency 4/4		0 %
Electric current	A	4,5 A	Speed	rpm	2950
Electric voltage	V	230 V	1~	Hz	50
Starting mode		Unknown			
Degree of protection		IP 44	Insulation class		F

Dimensions in mm

a	46
DNA	G 1"
DNM	G 1"
f	254
h1	98
h2	135
n1	180
n2	140
od	9
w	72



Remarks:

Project	Project ID	Created by	Created on	Last update
			2019-02-13	