



| ELECTRIC STORAGE WATER HEATERS WITH CERAMIC HEATING ELEMENTS | | | | | | | | | |
|--|-----------|----------|----------|----------|----------|----------|----------|---------|---------|
| CHARACTERISTICS | | | | | | | | | |
| Model | ... | WV05039C | WV08039C | WV08046C | WV10046C | WV12046C | WV15046C | 72280DC | 72281DC |
| Volume range | ... | 50 | 80 | 80 | 100 | 120 | 150 | 150 | 200 |
| Load profile | ... | M | M | M | M | M | L | L | L |
| Water heating energy efficiency class | ... | C | C | C | C | C | C | C | C |
| Annual electricity consumption | kWh/annum | 1401 | 1375 | 1366 | 1343 | 1333 | 2555 | 2544 | 2506 |
| Thermostat temperature presetting | °C | 60 | 60 | 60 | 60 | 60 | 60 | 60 | 60 |
| Mixed water at 40 °C | L | 70 | 118 | 120 | 144 | 188 | 217 | 217 | 322 |
| Rated pressure | MPa | 0.7 | 0.7 | 0.7 | 0.7 | 0.7 | 0.7 | 0.7 | 0.7 |
| Rated voltage | V~ | 230 | 230 | 230 | 230 | 230 | 230 | 230 | 230 |
| Rated power | kW | 2 | 2 | 2 | 2 | 2 | 2.2 | 2.2 | 2.2 |
| Weight with packing | kg | 21.5 | 30 | 28 | 33 | 37 | 44.5 | 52 | 64 |
| CONNECTIONS | | | | | | | | | |
| 1: Hot water outlet | | G1/2 M | G1/2 M | G1/2 M | G1/2 M | G1/2 M | G1/2 M | G1/2 M | G1/2 M |
| 2: Cold water inlet - Drain | | G1/2 M | G1/2 M | G1/2 M | G1/2 M | G1/2 M | G1/2 M | G1/2 M | G1/2 M |
| 3: Temperature indicator | | • | • | • | • | • | • | • | • |
| 4: External thermostat | | • | • | • | • | • | • | • | • |
| 5: Flange with heating element | | • | • | • | • | • | • | • | • |
| 6: Illuminated switch | | • | • | • | • | • | • | • | • |
| DIMENSIONS | | | | | | | | | |
| A | mm | 760 | 1125 | 835 | 1005 | 1170 | 1420 | 1015 | 1255 |
| C | mm | 155 | 155 | 185 | 185 | 185 | 185 | 190 | 190 |
| D | mm | 387 | 387 | 462 | 462 | 462 | 462 | 586 | 586 |
| E | mm | 80 | 80 | 96 | 96 | 96 | 96 | 105 | 105 |
| F | mm | 410 | 410 | 484 | 484 | 484 | 484 | 600 | 600 |
| G | mm | 33 | 33 | 33 | 33 | 33 | 33 | 43 | 43 |