



ELECTRIC STORAGE WATER HEATERS WITH DRY TUBULAR HEATING ELEMENTS								
CHARACTERISTICS								
Model	...	WV03039D	WV05039D	WV08039D	WV08046D	WV10046D	WV12046D	WV15046D
Volume range	...	30	50	80	80	100	120	150
Load profile	...	S	M	M	M	M	M	L
Water heating energy efficiency class	...	C	C	C	C	C	C	C
Annual electricity consumption	kWh/annum	548	1401	1375	1366	1343	1333	2555
Thermostat temperature presetting	°C	60	60	60	60	60	60	60
Mixed water at 40 °C	L	-	70	118	120	144	188	217
Rated presure	MPa	0.7	0.7	0.7	0.7	0.7	0.7	0.7
Rated voltage	V~	230	230	230	230	230	230	230
Rated electrical power	kW	2x0,8	2x0,8	2x1,0	2x1,0	2x1,0	2x1,0	2x1,0
Weight with packing	kg	15.5	20	28.5	26.5	31.5	36	43
CONNECTIONS								
1: Hot water outlet		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
2: Cold water inlet - Drain		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
3: Temperature indicator		•	•	•	•	•	•	•
4: External thermostat		•	•	•	•	•	•	•
5: Flange with heating elements		•	•	•	•	•	•	•
6: Illuminated switch		•	•	•	•	•	•	•
DIMENSIONS								
A	mm	560	760	1125	835	1005	1170	1420
C	mm	155	155	155	185	185	185	185
D	mm	387	387	387	462	462	462	462
E	mm	80	80	80	96	96	96	96
F	mm	410	410	410	484	484	484	484
G	mm	33	33	33	33	33	33	33

D - water heater with two dry tubular electric heating elements